

UHF RFID Cable Tie Tag



Quick Details

LDR-TZ02 UHF RFID Cable Tie Tag is designed as a zip. It is made of ABS and nylon material which can work in tough environment and with long lifespan and waterproof. It is disposable that cannot be separated after zipped. It can realize the track management of goods, meat and baggage.

Description

RFID Parameter	
Model No.	LDR-TZ02
Type	Passive UHF RFID Hard Tag
Protocol	ISO/IEC 18000-6C, EPC Class1 Gen2
Frequency	Worldwide 840-960Mhz
Chip	Ucode 9
Memory	EPC 96bits
	TID 48bits
	User 0bits

Read&Write	Supported
Read Range	0.5-1meters adjustable (reader and environment dependent)
Data retention	10years
Programming Cycles	100,000 cycles
Anti-collision	Yes
Physical Parameter	
Color	Green, Blue, Red, Other color can be customize
Size	72x28x3.6mm (LxWxH) , Total length:425mm
Antenna Material	PET+ Aluminum Etching
Surface Material	ABS + Nylon
Installation	Zip Tie Seal, Inseparable when zipped
Operating temperature	-25°C ~ +65°C
Operating humidity	20% ~ 90%RH
Package	50pcs/pack
Customized Service	Printing, EPC Pre-written, Color

Application

- ✓ RFID Pork tracking & Fresh Guarantee
- ✓ Logistic Seal Packages, Airport baggage tracking
- ✓ Tough environment that needs to zip



Size: 72x28x3.6mm (LxWxH) , Total length: 425mm