

# ISO14443A RS232 Reader Writer



**Model NO.: LDF-R1036S**

**Size: 123mmx94mmx29mm**

**N.W: 144g**


## **Specification**

- Comply with ISO14443TypeA protocol, supporting Mifare S50, S70, UltraLight and

related compatible cards, in addition to support reading and writing operation of DESFire, CPU and other types of CARDS.

- Advanced tag processing algorithm,high identification rate;
- Built-in TX/RX antenna with effective distance up to 100mm \*;
- Low power dissipation design with single DC+12V power source needed;
- Support TCP/IP and RS232 interface and provide DLL and demonstration software to facilitate development;
- Provide DLL and demonstration software to facilitate development.

## Interfaces



### Absolute Maximum Rating

ITEM	SYMBOL	VALUE	UNIT
Power Supply	VCC	12	V
Operating Temp.	T <sub>OPR</sub>	-10~+60	°C
Storage Temp.	T <sub>STR</sub>	-25~+80	°C

### Electrical and Mechanical Specification

Under T<sub>A</sub>=25°C, VCC=+12V unless specified

ITEM	SYMBOL	MIN	TYP	MAX	UNIT
Power Supply	VCC	11.5	12	15	V
Current Dissipation	I <sub>C</sub>		150	200	mA
Frequency	F <sub>REQ</sub>		13.56		MHz
Effective Distance*	DIS	0	80	100	mm

\*Effective distance depends on tag and working environment.