

5313 ON METAL TAG

A classic UHF Tag used on metal surfaces

It does a stable and reliable UHF on metal tag, which is widely used in indoor asset management.

ADVANTAGES:

- Be of good RF performance.
- 4 100% memory writing tested.
- Both material and design have been tested for reliability.
- 100% function tested by Voyantec
 Tagformace.

MAIN FEATURES:

- Can customize size for customers.
- Logo and photo can be printed on the surface of tag.
- Can be lasered with barcode and serial number.
- Flexible and convenient installation.

APPLICATIONS:

- 🐇 Storage management.
- 4 🛛 IT equipment management.
- Metal containers management.
- Metal equipment management.
- Personnel patrol management.
- Fixed asset management.
- Tool management



(S) +86 755 89379391 89379456

CHARACTERISTICS	-
Compliance	EPC Class1 Gen2; ISO18000-6C
Frequency	902-928MHz , 865~868MHz (Can
	customize frequency)
Chip	Impinj M4QT
Memory	EPC 128bits
Read/write	Yes
Data Storage	50 years
Warranty	One year
Material	FR4
Dimension	53mm L x 13mm W x 3.4mm H, hole1.5mm
Storage Temperature	-40 °C~ +110°C
Operating Temperature	-25 ℃~ +70 ℃
Storage humidity	5%~95%
Delivery format	Single
Installation Method	3M300LSE tape
Weight	~ 10g
Package	Bubble bag and carton
Color	Black
Power Supply	Passive
Drop Test	1 meters high, 200 drop test passed
Alcohol test	95% alcohol test passed
Gasoline test	Passed
High & low temperature	-40 °C ~ +70°C, 7 cycles, total 48 hours
shock test	
Temperature cycle test	-40°C~+70°C, 7 times cycle time testing,
	48 hours total
RoHS	Compatible
Read distance on metal surface	Up to 3 meters (EIRP=4W Alien9900 fixed reader)
Suildle	Up to 1.5 meters (With Alien9011 handheld
	reader)
RF performance	100% tested by Voyantic Tagformace
consistency test	
Options	Surface laser, surface LOGO screen printing,
	pre-encoding, surface pattern processing,
	surface painting, surface printing.

⊠ sales@leadercolor.com

www.leadercolor.com

(2) 2F, Building A11, No.6 Xinfeng Road, Taizhong Industrial Zone, Longgang District, Shenzhen China 518172